

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
25 September 2003 (25.09.2003)


PCT

(10) International Publication Number
WO 03/078851 A1

- (51) International Patent Classification⁷: **F16B 5/12**,
B60R 13/02
- (21) International Application Number: PCT/US03/07429
- (22) International Filing Date: 12 March 2003 (12.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/364,374 14 March 2002 (14.03.2002) US
- (71) Applicant (for all designated States except US): **INTIER
AUTOMOTIVE INC.** [CA/CA]; 521 Newpark Boulevard,
Newmarket, Ontario L3Y 4X7 (CA).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **FRITSCH, Man-
fred** [DE/US]; 4501 Woodcock Way, Highland, MI 48357
(US). **LAVALLEY, James, A.** [US/US]; 1513 N. Vernon,
Dearborn, MI 48128 (US). **WENGLINSKI, Daniel, E.**
[US/US]; 8025 Lincoln, Taylor, MI 48180 (US).
- (74) Agents: **RASHID, Peter, J.** et al.; Rader, Fishman &
Grauer PLLC, 39533 Woodward Avenue, Suite 140,
Bloomfield Hills, MI 48304 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: TWO STAGE ATTACHMENT ANCHOR



(57) Abstract: A connector assembly for attaching a hardware component and a trim panel to a vehicular structure includes a shank (18) and a head (20). The shank has a head end (22) and an anchor end (24) for securing the hardware component to the vehicular structure. The head has a trim retaining end and a shank engaging end (42). The trim retaining end secures the connector assembly (10) to a trim panel. A break neck (50) is disposed between the shank engaging end and the trim retaining end of the head. Upon application of a load to the head, the head breaks from the shank at the break neck, allowing the removal of the trim panel from the hardware component and the vehicular structure.

WO 03/078851 A1